www.tripplite.com



Surge Suppressor- State of the art protection for every application

MODEL NUMBER: S6-DLX



Description

The S6-DLX Surge Suppressor from Tripp Lite has 6 outlets and a 6-ft. cord with a space-saving right-angle plug. The unit has 1,050 joules of surge energy absorption to handle the strongest surges. Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment. A telephone cord is also included. Diagnostic LEDs alert the user to potential power problems. \$15,000 Ultimate Lifetime Insurance (USA & Canada Only). No warranty cards required for coverage! The Super 6 Deluxe comes with child safety covers and color-coded cord identifiers.

Features

- 6 outlets with child safety covers
- 6-ft. cord with space-saving right-angle plug
- Built-in RJ11 jacks prevent surges from damaging your modem / fax / phone equipment; 6-ft. telephone cord included
- \$15,000 Ultimate Lifetime Insurance (USA & Canada Only) covers connected equipment No warranty cards required for coverage!
- Surge energy absorption: 1,050 joules; 42,500 amps
- 15 amp circuit breaker
- 2 diagnostic LEDs indicate AC present & line fault
- EMI/RFI noise filtering
- Keyhole supports for wall mounting
- · Color-coded cord identifiers
- Lifetime product warranty

Specifications

Highlights

- 6 outlets/6 ft. cord
- 1050 joule rating
- Modem/fax surge protection
- \$15,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

Package Includes

- S6-DLX Surge Suppressor
- Telephone cord
- Child Safety Covers
- · Color-coded cord identifiers
- Warranty information with instruction manual



OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output Receptacles	(6) 5-15R	
Output (Watts)	1800	
Circuit Breaker (amps)	15	
Transformer Accommodation	Holds up to 3 large transformer plugs	
INPUT		
Nominal Input Voltage(s) Supported	100V AC	
Recommended Electrical Service	120V (110-125V)	
Input Connection Type	NEMA 5-15P input plug	
Input Cord Length (ft.)	6	
Input Cord Length (m)	1.83	
Voltage Compatibility (VAC)	120	
Right-Angle Plug	Yes	
USER INTERFACE, ALERTS & CONTROLS		
Switches	Two position on/off power switch	
Diagnostic LED Details	PROTECTION PRESENT, LINE OK	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1050	
AC Suppression Response Time	< 1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping Voltage (RMS)	150	
AC Suppression Surge Current Rating	42,500 amps	
UL1449 Let Through Rating	330V - UL Verified	
Immunity	Conforms to IEE 587 / ANSI C62.41	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	Yes	
Telephone/DSL Protection Details	1 line	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		





Unit Dimensions (hwd / in.)	1.25 x 3.25 x 8.25	
Unit Dimensions (hwd / cm)	3.2 x 8.3 x 21	
Material of Construction	Plastic	
Integrated Keyhole Mounting Tabs	Keyhole mounting tabs enable wall mounting	
Housing Color	Gray	
Receptacle Color	Gray	
Color (AC Line Cord)	Gray	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449	
UL1363 (Power Tap)	UL1363	
UL497A (Communications)	UL497A	
FCC Part 68 (Communications)	FCC Part 68	
cUL / CSA (Canada)	cUL	
Industry Canada (Communications)	Industry Canada	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$15,000 Ultimate Lifetime Insurance	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies